

# Web Grader WG 900

Gentle grading for more success throughout  
the whole line



# Grading means winning

The crop is usually in various shapes and sizes but for the market a consistent size and quality is required. To meet these demands the Web Grader is the solution for your handling line. For gentle grading into various sizes of potatoes, onions

or other crops. No matter if you prefer a single machine or an integrated unit, with the Grimme Web Grader WG 900 you have the choice of more success through the whole line.

WG 900 STAND ALONE

## Successful storing: gentle grading, careful transporting

*Accurate and gentle: Grimme Web Grader (1) with a 900 mm wide rubber web. Convenient as either mobile by use of swivel wheels or static and moved via a fork lift. Infinite drive, special transfer roller and a very low drop height over cushioned deflector plates care for a gentle handling of the crop.*





*Gentle transfer: rubber discharge chutes (2) or cross conveyor (1) as option forward the crop to the next station. Grading webs (3) in various sizes are available.*

*An agitator under the web (4) avoids crop blocking under the web.*

*The agitator speed is infinitely adjustable and independent to the web speed. For gentle grading either for long or round crop.*

*The yellow paddle roller for gentle lifting of the crop from the web. An additional roller (5) avoids stone and haulm blockage.*





WG 900 UNIT IN A GRADING LINE

## Single or as a double: the powerful unit in a grading line



*Stronger in a team: combine the high output of the grading roller with the accuracy of the following Web Grader.*



*Depending on the model (1) it is possible to integrate one or two Web Graders (side by side) (2) following the grading unit at the RH-Combi. Please ask for advice.*



*The modular design of the WG 900 allows a set-up of several Web Graders in a line (3). For gentle grading of small to big crop. To use the whole width of the Web Grader for grading the machine has especially wide cross conveyor.*



## Technical data

	WG 900 with discharge	WG 900 with additional crop cross conveyor
<b>Measurements</b>		
<b>Length</b>	2,700 mm	2,700 mm
<b>Width</b>	2,150 mm	2,150 mm
<b>Height</b>	1,375–1,600 mm	1,375–1,600 mm
<b>Weight</b>	880 kg (standard machine)	960 kg
<b>Belt speed</b>	5–30 m/min	5–30 m/min
<b>Cross conveyor speed</b> <b>Crop cross conveyor</b>	–	5–25 m/min
<b>Intake height</b>	Minimal 1,075 mm Maximal 1,300 mm (adoption on request)	Minimal 1,075 mm Maximal 1,300 mm (adoption on request)
<b>Discharge height</b>	Minimal 675 mm Maximal 900 mm	Minimal 725 mm Maximal 950 mm
<b>Web Grader length</b>	1,850 mm	1,850 mm
<b>Effective grading length</b>	1,500 mm	1,500 mm
<b>Effective grading width</b>	900 mm	900 mm

Successful through the whole line: with winning handling technology from Grimme



Receiving Hoppers



Single- and Twin conveyors



Store Loaders



Combi Unit Picking/Separating unit



Box filler



Web Grader

Your Grimme Partner for advice and service:

**GRIMME**  
HARVESTING SUCCESS!

Grimme Landmaschinenfabrik GmbH & Co. KG · Hunteburger Straße 32 · D-49401 Damme  
Phone +49 5491 666-0 · Fax +49 5491 666-2298  
grimme@grimme.de · www.grimme.com